

BellSouth Service Quality Measurement Plan (SQM)

Kentucky Performance Metrics

**Measurement Descriptions
Version 3.0506**

Effective Date: ~~May 29~~July 3, 2010

Note: This SQM version is issued to reflect the OSS architecture changes implemented on ~~May 29~~July 3, 2010.

Introduction

BellSouth Service Quality Measurement Plan (SQM) describes in detail the measurements produced to evaluate the quality of service delivered to BellSouth's wholesale customers. The SQM was developed to respond to the requirements of the Communications Act of 1996 Section 251 (96 Act) which required BellSouth to provide non-discriminatory access to Competitive Local Exchange Carriers (CLEC)¹. The reports produced by the SQM provide regulators, CLECs and BellSouth the information necessary to monitor the delivery of non-discriminatory access.

The Georgia Public Service Commission issued its *Order Granting Joint Motion to Approve New Performance Measurement Plan* on July 18, 2005, and this plan includes the same SQM approved by the Georgia Commission. This SQM is to be implemented by BellSouth pursuant to orders issued by the Kentucky Public Service Commission (the "Commission") in Docket No. 2004-00391 (dated June 20, 2005) and in Docket No. 2001-00105 (dated May 11, 2004) instructing BellSouth to continue with the Georgia performance plan, along with any future modifications. This SQM includes modifications resulting from the implementation of OSS architecture changes on April 19, 2008, July 18, 2009, November 14, 2009, April 15, 2010, ~~and~~ May 29, 2010, and July 3, 2010.

The SQM and the reports flowing from it must change to reflect the dynamic requirements of the industry. New measurements are added as new products, systems, and processes are developed and fielded. New products and services are added as the markets develop and the processes stabilize. The measurements will be changed to reflect the dynamic changes described above and to correct errors, respond to 3rd Party audits, Orders of the KPSC, FCC and the appropriate Courts of Law.

This document is intended for use by someone with knowledge of the telecommunications industry, information technologies and a functional knowledge of the subject areas covered by BellSouth Performance Measurements and the reports that flow from them.

Report Publication Dates

Each month, preliminary SQM reports will be posted to BellSouth's PMAP website (<http://pmap.bellsouth.com>) by 8:00 AM EST on the 21st day of each month or the first business day after the 21st. The validated SQM reports will be posted by 8:00 AM on the last day of the month or the first business day after the last day of the month.

For details on SEEM, please refer to the SEEM Administrative Plan.

BellSouth shall retain the performance measurement Supporting Data Files (SDF) for a period of 18 months and further retain the monthly reports produced in PMAP for a period of three years. Instructions for replicating the reports in the SQM are contained in the Supporting Data User Manual (SDUM). The SDUM is available on the PMAP website and is automatically provided with each SDF download.

¹Alternative Local Exchange Companies (ALEC) and Competing Local Providers (CLP) are referred to as Competitive Local Exchange Carriers (CLEC) in this document.

CM-5 [ION]: Notification of CLEC Interface Outages

Definition

This report measures the time it takes BellSouth to notify the CLECs of an interface outage as defined by the Change Control Process (CCP) documentation.

Exclusions

None

Business Rules

BellSouth has 15 minutes to notify the CLECs via email, once the Help Desk has verified the existence of an outage. An outage is verified to exist when one or more of the following conditions occur:

1. BellSouth can duplicate a CLEC reported system error.
2. BellSouth finds an error message within the error log that identically matches a CLEC reported system outage.
3. When three or more CLECs report the identical type of outage.
4. BellSouth detects a problem due to the loss of functionality for users of a system.

The 15-minute interval begins once a CLEC reported outage or a BellSouth detected outage has lasted for 20 minutes and has been verified. If the outage is not verified within 20 minutes, the interval begins at the point of verification.

Calculation

Notification of CLEC Interface Outages = (a / b) X 100

- a = Number of interface outages where CLECs are notified within 15 minutes
- b = Total number of interface outages

Report Structure

- CLEC Aggregate
- Geographic Scope
Region

SQM Disaggregation - Analog/Benchmark

SQM Level of Disaggregation

- By interface type for all interfaces accessed by CLECs97% <= 15 Minutes

SQM Analog/Benchmark

Interface	Applicable to
CSOTS.....	CLEC
<u>LENS</u>	<u>CLEC</u>
LEX.....	CLEC
Verigate.....	CLEC
XML Gateway.....	CLEC
EBTA.....	CLEC
TAFI.....	CLEC/BellSouth

SEEM	Tier I	Tier II
No.....		

G H

HDSL

High Bit Digital Subscriber Line – A dedicated digital transmission facility from BellSouth’s Main Distribution Frame (MDF) to an end user’s premises.

I J K

ILEC

Incumbent Local Exchange Carrier – Regional Bell Operating Company (RBOC)

INP

Interim Number Portability – When the customer is originally provided service by an ILEC and decides to change service to a CLEC, the customer may retain their ILEC telephone number. Calls to the ILEC number are rerouted to the CLEC using either the Remote Call Forwarding feature or over a dedicated trunk group from the ILEC switch to the CLEC

ISDN

Integrated Services Digital Network – An integrated digital network in which the same time-division switches and digital transmission paths are used to establish connections for different services. ISDN services include telephone, data, electronic mail, and facsimile.

L

LAN

Local Area Network – A data communications system that lies within a limited spatial area, has a specific user group, has a specific topology, and is not a public switched telecommunications network, but may be connected to one.

LASR

Local Access Service Request-Negotiation system for entry and processing of Local Service Requests. Stores all LSRs received mechanically from CLECs. Tracks status of request and all service orders.

LAUTO

The automatic processor in LNP Gateway that validates LSRs and issues service orders.

LCSC

Local Carrier Service Center - The BellSouth center which is dedicated to handling CLEC LSRs and preordering transactions, along with associated expedite requests and escalations.

Legacy System

Term used to refer to BellSouth Operations Support Systems.

LENS

~~Local Exchange Navigation System – The BellSouth application developed to provide both preordering and ordering electronic interface functions for CLECs.~~

LERG

Local Exchange Routing Guide – The official document which lists all North American Class 5 office (COs or end offices) and which describes their relationship to Class 4 office (tandem offices). Carriers use the LERG in the network design process.

LESOG

Local Exchange Service Order Generator - A BellSouth system which accepts the service order output of LASR and enters the service order into the Service Order Control System using terminal emulation technology.

LEX

Local Service Request Exchange (LEX) System – An AT&T browser based application for online creation, submittal, and maintenance of Local Service Requests (LSRs).

Appendix C: OSS Interface Tables

OSS-1 [PRR]: OSS Response Interval (Pre-Ordering/Ordering/Maintenance & Repair)

Table 1: Legacy System Access Times For RNS

System	Contract	Data	Avg. Sec.	# of Calls
RSAG	RSAG-TN	Address	X	X
RSAG	RSAG-ADDR	Address	X	X
ATLAS	ATLAS-TN	TN	X	X
DSAP	DSAP-DDI	Schedule	X	X
CRIS	CRSACCTS	CSR	X	X
OASIS	OASISBIG	Feature/Service	X	X

Table 2: Legacy System Access Times For R0S

System	Contract	Data	Avg. sec.	# of Calls
RSAG	RSAG-TN	Address	X	X
RSAG	RSAG-ADDR	Address	X	X
ATLAS	ATLAS-TN	TN	X	X
DSAP	DSAP-DDI	Schedule	X	X
CRIS	CRSOCSR	CSR	X	X
OASIS	OASISBIG	Feature/Service	X	X

Table 3: Legacy System Access Times For LENS/LEX/Enhanced Verigate (Pre-Order only)

System	Contract	Data	Avg. sec.	# of Calls
RSAG	RSAG-TN	Address	X	X
RSAG	RSAG-ADDR	Address	X	X
ATLAS	ATLAS-TN	TN	X	X
DSAP	DSAP-DDI	Schedule	X	X
CRIS	CRSECSRL	CSR	X	X
COFFI	COFFI/USOC	Feature/Service	X	X
P/SIMS	PSIMS/ORB	Feature/Service	X	X

Table 4: Legacy System Access Times For XML Gateway

System	Contract	Data	Avg. sec.	# of Calls
RSAG	RSAG-TN	Address	X	X
RSAG	RSAG-ADDR	Address	X	X
ATLAS	ATLAS-TN	TN	X	X
ATLAS	ATLAS-MLH	TN	X	X
ATLAS	ATLAS-DID	TN	X	X
DSAP	DSAP-DDI	Schedule	X	X
CRIS	CRSECSRL	CSR	X	X
P/SIMS	PSIM/ORB	Feature/Service	X	X

Table 5: Legacy System Access Times for M&R (TAFI)

System	BellSouth & CLEC	Count <= 10
CRIS	x	x
DLETH	x	x
DLR	x	x
LMOS	x	x
LMOSupd	x	x
LNP Gateway	x	x
MARCH	x	x
OSPCM	x	x
Predictor	x	x
SOCS	x	x
NIW	x	x

OSS-2 [IA]: OSS Interface Availability (Pre-Ordering/Ordering/Maintenance & Repair)

OSS Table 1: SQM Interface Availability for Pre-Ordering/Ordering

OSS Interface Availability Application	Applicable to	% Availability
<u>LENS</u>	<u>CLEC</u>	x
LEX	CLEC	x
LASR	CLEC	x
WFM	CLEC	x
OBF	CLEC	x
Enhanced Verigate	CLEC	x
LESOG	CLEC	x
XML Gateway	CLEC	x
LNP Gateway	CLEC	x
COG	CLEC	x
SGG	CLEC	x
DOE	CLEC/BellSouth	x
SONGS	CLEC/BellSouth	x
ATLAS/COFFI	CLEC/BellSouth	x
BOCRIS/CRIS	CLEC/BellSouth	x
DSAP	CLEC/BellSouth	x
RSAG	CLEC/BellSouth	x
SOCS	CLEC/BellSouth	x
LFACS	CLEC/BellSouth	x
RNS	BellSouth	x
ROS	BellSouth	x